

LTM-eGX

BATTERY DRIVEN WALK BEHIND POWER TROWEL

Effortless emission-free floating and finishing of concrete floors.

Description

The Lievers LTM power trowel has long been the choice of professionals when it comes to top quality, technology, the LTM can now also be used as a cordless, emission-free machine, making it suitable for indoor work too. The noise emissions from the **LTM eGX trowels** are several times lower than those of its gasoline powered counterparts.



Most important features:

- **Cordless, emission-free operation**
- **72V Honda battery-powered motor** with belt drive and high-efficiency gearbox
- **720Wh battery pack** for the motor
- **High performance, speed regulated electric motors** combined with **high performance gearboxes**.
- The **steering handle** is **height-adjustable** and has a narrow profile making the machine ideal for residential construction.
- The width of the **steering handle** is customizable to taste (for **LTM 600eGX** & **LTM 750eGX**).

- The **pitch control** is now even **easier to reach**, so blade adjustment is faster and more comfortable.
- The trowel arms are standard equipped with **grease nipples**, for easy periodic maintenance.
- The **handle folds away easily**. Minimizing the necessary storage space and optimising transport.
- **Cooler operating** of the gearbox increases lifetime and **decreases service interval**.
- The rotating guard ring on **LTM 600eGX** and **LTM 750eGX** guide the machine along walls and obstacles.



Detail picture eGX Engine



Detail picture steering handle LTM-eGX

Specifications:

	LTM 600eGX	LTM 750eGX
MOTOR	HONDA eGX	HONDA eGX
VOLTAGE	72V DC	72V DC
MOTOR POWER	1.8kW	1.8kW
BATTERY	72V 720 Wh	72V 720 Wh
BLADE SPEED	40 – 144 rpm	40 – 144 rpm
DIAMETER DISC	Ø600 mm	Ø750 mm
WEIGHT	68 kg (incl. battery)	76.5 kg (incl. battery)
BATTERY SYSTEM	Lithium-Ion/72V DC	Lithium-Ion/72V DC
CHARGING TIME	Max. 90 minutes	Max. 90 minutes
BATTERY WEIGHT	6.8kg	6.8kg