

PREFAB EASY SCREED

Rev. 2/17-06-2013

SCREED

For excellent finishing of prefab elements.

Description

PREFAB EASY SCREED is an easy-to-use screed especially useful for levelling of prefab elements. This screed consists of an electrical drive unit with speed regulator, a lightweight beam, a user friendly clamping system for easy changing of beam lengths and 2 carrying handles. The drive unit is standard available in 230V / 50-60 Hz. On request available in 115V / 50-60 Hz.

Characteristics

Main characteristics of the PREFAB EASY SCREED are:

- Lightweight beams available in various lengths.
- Driven by a powerful, double insulated (IP54 isolation class) electrical drive unit, which is interchangeable with all beam lengths.
- Equipped with an electronic speed regulator, which enables the operator to set the required vibrations with regard to the concrete consistency.
- Equipped with removable handles and a user friendly clamping system, which allows easy exchanging of beams.
- The machine is light in use and realises an excellent flat result.



Technical information

BEAM LENGTHS	WEIGHT BEAM (EXCL. DRIVE UNIT)	FREQUENCY	ELECTRICAL DRIVE UNIT		TOTAL WEIGHT
			Power	Voltage	Weight
meter	Kg	RPM			
1.52	4.4	Up to 11.000	350 W	230V 50-60 Hz	16.9 kg
1.83	5.3	Up to 11.000	350 W	230V 50-60 Hz	17.8 kg
2.44	7.1	Up to 11.000	350 W	230V 50-60 Hz	19.6 kg
3.05	8.8	Up to 11.000	350 W	230V 50-60 Hz	21.3 kg
3.66	10.6	Up to 11.000	350 W	230V 50-60 Hz	23.1 kg
4.27	12.4	Up to 11.000	350 W	230V 50-60 Hz	24.9 kg
4.88	14.2	Up to 11.000	350 W	230V 50-60 Hz	27.7 kg